



## **RVSK112 FUEL WATER SEPARATOR / CATCHCAN FITMENT INSTRUCTIONS**

**MITSUBISHI TRITON MQ / MR / PAJERO SPORT - See RYCO catalogue for specific application details.**


The Ryco RVSK112 kit includes mounting bracket specifically designed for the vehicle, and all components required to complete the installation of Ryco Z980SK series fuel water separator and RCC351 series catchcan (both sold separately). It is recommended that the installation is conducted by a qualified mechanic following the procedures in this instruction sheet.




### **SECTION 2 FUEL WATER SEPARATOR (SOLD SEPARATELY)**




### **SECTION 4 CATCHCAN (SOLD SEPARATELY)**



### **SECTION 1 FUEL MOUNTING BRACKET (INCLUDED IN RVSK112)**




### **SECTION 3 CATCHCAN MOUNTING BRACKET (INCLUDED IN RVSK112)**




**COMPONENTS INCLUDED IN RVSK112 KIT**  
(Components not sold SEPARATELY)

**PARTS LIST - FUEL FILTER BRACKET & COMPONENTS BOX**




**PARTS LIST - PACKAGED IN CARTON**




**COMPONENTS INCLUDED IN RVSK112 KIT**  
(Components not sold SEPARATELY)

**PARTS LIST - CATCHCAN BRACKET & COMPONENTS BOX**

MS4089  
PVC HOSE x 1M



MS4091  
PCV HOSE CLAMP x 2




MS4037A  
HEX BOLT x 1 (M6 - 35MM)




MS4106  
FLAT WASHER x 1 (M6)



MS4040  
FLANGE NUT x 2 (M6)



MS4094  
PCV HOSE CLAMP x 2




MS4107  
SPRING WASHER x 1 (M6)




MS4093  
DRAIN HOSE CLAMP x 2




MS4090  
DRAIN VALVE x 1



**PARTS LIST - PACKAGED IN CARTON**




MH9810A  
PCV HOSE x 1



MH9810B  
PCV HOSE x 1



NYLON BRACKET x 1




FB9810CC  
CATCHCAN MOUNTING BRACKET x 1

## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 1 FUEL MOUNTING BRACKET FITMENT (1/4)

#### PARTS REQUIRED



#### TOOLS & PPE'S REQUIRED

- \* WORK GLOVES
- \* SOCKET SET
- \* RATCHET SET

#### WORK PROCEDURE

1. Unclip all OEM fuel filter Deutsch connectors from the OEM fuel filter bracket
2. Disconnect OEM Male & Femal Deutsch connectors
3. Remove the OEM fuel filter housing from the OEM fuel filter bracket by lifting it up out of its slot, then place it to left hand side of the bracket.
4. Unscrew the 2 x OEM M8 bolts shown in Fig. 2a. Ensure you hold onto these M8 bolts, as you will be using these to fit the FB9810FC bracket later.





FIG. 1 OEM FUEL HOUSING REMOVAL



## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 1 FUEL MOUNTING BRACKET FITMENT (2/4)

#### WORK PROCEDURE

5. Unscrew the OEM M8 bolt shown in Fig. 2b. Place this M8 bolt with the other 2 OEM M8 bolts as you will be using these to fit the supplied FB9810FC bracket later.
6. Remove the OEM fuel supply hose & hose clamps (highlighted green in Fig. 3). Have a rag ready as some fuel will spill from the hose and pipe.
7. Half screw in 2 of the OEM M8 bolts saved from the previous steps in to the base mounting point as shown in Fig. 4a. (Screw in enough to allow Ryco FB9810FC bracket to slide in).
8. Slide the RYCO FB9810FC bracket so bottom two slots of the bracket engage the half screwed in OEM M8 Bolts.




FIG. 2b OEM FUEL BRACKET REMOVAL




FIG. 3 OEM INLET FUEL HOSE REMOVAL




FIG. 4a FB9810FC BRACKET INSTALLATION

## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 1 FUEL MOUNTING BRACKET FITMENT

(3/4)

#### WORK PROCEDURE

9. Screw in the remaining OEM M8 bolt saved from the previous steps in to the firewall mounting point. Then install the supplied MS4040 M6 flange nut on to the firewall stud as shown in Fig. 4b.

MS4040 M6  
Flange Nut

OEM M8 Bolt




FIG. 4b FB9810FC BRACKET INSTALLATION

10. Proceed to fully tighten the OEM M8 Bolts shown in Fig. 4c.



FIG. 4c FB9810FC BRACKET INSTALLATION

11. Install the OEM Fuel Filter Housing by first passing the female OEM Deutsch connector#1 through the opening as shown in Fig.5a. Then mount the OEM fuel filter housing on to its mounting slot as shown in Fig.5a.

OEM Fuel Filter  
Housing

OEM Female Deutsch  
Connector#1





FIG. 5a OEM HOUSING INSTALLATION

## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 1 FUEL MOUNTING BRACKET FITMENT (4/4)

#### WORK PROCEDURE

12. Clip the female OEM Deutsch connect#1 on to the slot as shown in Fig.5b.




13. Connect the Male and Female OEM Deutsch connector#1 then cable tie the OEM Deutsch connector#1 loom to the slot on the FB9810FC bracket as shown in FIG. 5c

Male OEM Deutsch  
Connector#1 Loom

Cable Tie

Female OEM Deutch  
Connector #2

Male OEM Deutsch  
Connector#1



14. Clip the Female OEM Deutsch connector#2 to the slot on the FB9810FC bracket as shown in Fig. 5c.

## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 2 FUEL WATER SEPARATOR INSTALLATION

PARTS REQUIRED		TOOLS & PPE'S REQUIRED
		<ul style="list-style-type: none"> <li>* WORK GLOVES</li> <li>* RACHET SET</li> <li>* HOSE CLAMP PLIERS</li> <li>* RAGS</li> </ul>

### WORK PROCEDURE (1/3)

1. Select the supplied male quick connectors (MS4086 or MS4096) that fit your Ryco fuel water separator head.
2. Locate the blanking plugs supplied with your Ryco fuel water separator.
3. Apply the supplied thread sealant to the thread of the blanking plugs and the quick connectors. Install them as per Fig. 3, ensuring they are tight.
4. Install two (2) supplied elbow connectors onto one end of both the supplied fuel hoses and install four (4) supplied fuel hose clamps onto each end of the fuel hoses, as per Fig. 4. Do not tighten the fuel hose clamps yet.




FIG. 3 FUEL WATER SEPARATOR HEAD PREPARATION


FIG. 4 FUEL HOSE PREPARATION

## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 2 FUEL MOUNTING BRACKET FITMENT (2/3)

#### WORK PROCEDURE

5. Using the M10 Bolts and Washers supplied in the Ryco Z980K fuel water separator kit, attach the Z980K to the FB9810FC bracket as shown in FIG. 6.
6. Starting with the longer Ryco fuel hose FH9810B, install the open end of the hose on to the vehicles fuel tank supply pipe, and tighten with the MS4041A hose clamp as shown in Fig. 7 (overleaf).
7. Route the hose around the front of the OE fuel filter housing and along the other side of the fuel filter assembly, shown as green in Fig. 7 (overleaf).  
Connect the MS4097 Elbow Connector to the Z980K Inlet Quick Connector.  
Connection has been successfully made when you hear a 'click' noise.




## RVSK112 FUEL WATER SEPARATOR FITMENT INSTRUCTIONS

### SECTION 2 FUEL MOUNTING BRACKET FITMENT (3/3)

#### WORK PROCEDURE


REFER TO FIG.7 DIAGRAM BELOW

8. With the shorter Ryco fuel hose FH9810A, install the open end of the hose on to the inlet port of OEM fuel filter housing and tighten with the MS4041A Hose Clamp.  
Route the hose, shown in yellow in Fig. 7. and connect the MS4097 Elbow Connector to the Z980K Outlet Quick Connector.  
Connection has be successfully made when you hear a 'click' noise.
9. **WARNING:** The fuel system **MUST BE PRIMED** prior to starting the engine.  
**DO NOT OPEN THE BLEED SCREW ON THE RYCO Z980K, keep closed.**
10. Locate the priming button on top of the factory fuel filter and prime the fuel system by pumping the button repeatedly. Continue pumping until it is hard to press.  
The priming process could take approximately 5 - 10 minutes.
11. Once you can no longer depress the priming button, turn on the engine.  
With the engine running, check for fuel leaks on all the installed equipment.



## RVSK112 CATCHCAN FITMENT INSTRUCTIONS

### SECTION 3 CATCHCAN INSTALLATION

PARTS REQUIRED	TOOLS & PPE'S REQUIRED
<div data-bbox="20 392 263 824">  <p>RCC351 CATCHCAN (SOLD SEPARATELY)</p> </div> <div data-bbox="263 392 782 824"> <p>MH9810A PCV HOSE x 1</p> <p>MH9800B PCV HOSE x 1</p> <p>MS4091 PCV HOSE CLAMP x 2</p> <p>MS4094 PCV HOSE CLAMP x 2</p> </div> <div data-bbox="782 392 1257 824"> <p>3MM NYLON BRACKET (OPTIONAL)</p> <p>MS4037A HEX BOLT x 1 (M6 - 35MM)</p> <p>MS4106 FLAT WASHER x 1 (M6)</p> <p>MS4107 SPRING WASHER x 1 (M6)</p> <p>MS4040 FLANGE NUT x 2 (M6)</p> </div>	<p><b>* WORK GLOVES</b></p> <p><b>* RACHET SET</b></p> <p><b>* HOSE CLAMP PLIERS</b></p>

### WORK PROCEDURE

1. Remove the plastic engine cover.
2. Remove OEM PCV hose highlighted green in FIG. 8a
3. Remove the OEM nut from the brake booster mounting stud as shown in Fig. 8a
4. Remove the rear airbox mounting OEM bolt & washer shown in FIG. 8b.




FIG. 8A OEM PCV HOSE REMOVAL

FIG. 8b AIRBOX MOUNTING OEM BOLT/WASHER REMOVAL

## RVSK112 CATCHCAN FITMENT INSTRUCTIONS

### SECTION 3 CATCHCAN INSTALLATION

#### WORK PROCEDURE

5. When fitting the FB9810CC Catchcan bracket as shown in FIG. 9A to 9C, you will be required to manoeuvre the bracket around engine components.




FIG. 9A FB9810CC BRACKET INSTALLATION

6. Referring to FIG. 9B, we recommend first engaging the bracket Slot B on to engine Stud B under the brake pipes. Then proceed to line up Slot A with Thread A behind the air box. Finally engage Slot C onto Firewall Stud C at the brake booster.




FIG. 9B FB9810CC SLOT/THREAD/STUD LOCATIONS





FIG. 9C FB9810CC BRACKET IN POSITION

## RVSK112 CATCHCAN FITMENT INSTRUCTIONS


### SECTION 3 CATCHCAN INSTALLATION

#### WORK PROCEDURE


7. Engage supplied MS4037A M6 bolt into supplied MS4107 M6 spring washer, MS4106 M6 washer & Slot A, proceeding to then screw into Airbox mount Thread A.



8. Screw supplied MS4040 M6 flange nut onto Stud B.



9. Screw supplied MS4040 M6 flange nut onto Stud C.



## RVSK112 CATCHCAN FITMENT INSTRUCTIONS

### SECTION 4 CATCHCAN INSTALLATION

#### WORK PROCEDURE

10. Slot Catchcan on to the FB9810CC Catchcan bracket as shown in FIG.

**NOTE:** If the plastic bracket supplied with your RCC351 has a 2mm slot, remove & replace with the plastic bracket supplied in the RVSK112 kit.




FIG. 11a CATCHCAN FITMENT

11. Proceed to rotate the RCC351 to match the alignment shown in FIG. 11b, ensuring clearance to the Engine Airbox.




FIG. 11b CATCHCAN FITMENT

## RVSK112 CATCHCAN FITMENT INSTRUCTIONS

### SECTION 4 CATCHCAN INSTALLATION

#### WORK PROCEDURE

REFER TO FIG. 11a & 11b

12. Starting with the MH9810B PCV hose, install the small end on to the Engine PCV Port & tighten with the MS4094 hose clamp as shown in Fig. 11a & 11b.
13. Install the other end of the MH9810B PCV hose on to the lower, inlet port, of the RCC351 Catchcan and tighten with the MS4091 hose clamp as shown in Fig. 11a & 11b.
14. Install the larger end of the MH9810A hose on to the upper, outlet port, of the RCC351 Cathcan and tighten with a MS4091 hose clamp. Install the other end of the MH9810A PCV hose on to the Air Intake PCV port and tighten with a MS4094 hose clamp as shown in Fig. 11a & 11b.




FIG. 11a PCV HOSE INSTALLATION DIAGRAM




FIG. 11b PCV HOSE INSTALLATION DIAGRAM


## **RVSK112 CATCHCAN FITMENT INSTRUCTIONS**

### **SECTION 4 CATCHCAN INSTALLATION (CONTINUED)**

#### **WORK PROCEDURE (CONTINUED)**

#### **DRAIN HOSE INSTALLATION PROCEDURE (OPTIONAL)**

1. To install the drain hose, remove the drain plug from the bottom of RCC351, take out the rubber seal from the plug and refit. Insert the drain hose and secure it with the supplied spring clamp. Insert the hose drain tap to the other end and use the zip ties to secure the hose. To drain, pull back the red section until all oil has drained out.
2. If it has been fitted without using the drain hose supplied, simply slide out the unit from its bracket and remove the drain plug on the unit and let the oil drain onto a pan or bottle.



**AUSTRALIA**  
RYCO Group Pty Ltd  
29 Taras Avenue, Altona North  
Victoria 3025 Australia.  
[www.rycofilters.com.au](http://www.rycofilters.com.au)

**NEW ZEALAND**  
RYCO Group - A division of GUD (NZ) Holdings Limited  
19 Bell Avenue, Otahuhu,  
Auckland, 1060 New Zealand.  
[www.ryco.co.nz](http://www.ryco.co.nz)

**SOCIAL NETWORKS**  
Facebook: <http://facebook.com/rycofilters>  
YouTube: <http://youtube.com/rycofilters1>  
Twitter: [http://twitter.com/Ryco\\_Filters](http://twitter.com/Ryco_Filters)